HU362RB

Safety switch, heavy duty, non fusible, 60A, 3 wire, 3 poles, 60hp, 600VAC/DC, Type 3R, bolt on hub provision





Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	3
Current Rating	60 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 3R galvannealed steel
Motor power hp	10 Hp at 240 V AC 50-60 Hz for 1 phase motors 20 Hp at 240 V AC 50-60 Hz for 3 phase motors 25 Hp at 480 V AC 50-60 Hz for 1 phase motors 50 Hp at 480 V AC 50-60 Hz for 3 phase motors 30 Hp at 600 V AC 50-60 Hz for 1 phase motors 60 Hp at 600 V AC 50-60 Hz for 3 phase motors 10 Hp at 250 V DC 30 hp at 600 V DC

Complementary

Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire
Wire Size	AWG 14AWG 3 copper AWG 12AWG 3 aluminium
Tightening torque	50 Lbf.In (5.65 N.m) (AWG 3) 45 Lbf.In (5.08 N.m) (AWG 6AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 50 lbf.in (5.65 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)
Depth	6.38 in (162.05 mm)
Width	10.5 in (266.70 mm)
Height	21.25 in (539.75 mm)
Net Weight	15.43 lb(US) (7 kg)

Environment

	III listed file F2075
Certifications	UL listed file E2875
OCI IIIIOGIIO113	OL IISICA IIIC EZOTO

Ordering and shipping details

Category	00009-H&HU SW,2&3P,N3R,30-200A
Discount Schedule	DE1
GTIN	785901505617
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.20 in (20.828 cm)
Package 1 Width	11.80 in (29.972 cm)
Package 1 Length	19.90 in (50.546 cm)
Package 1 Weight	15.20 lb(US) (6.895 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	40
Package 2 Height	45.50 in (115.57 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	646.00 lb(US) (293.02 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

_ constraint,	
Warranty	18 months

Approximate Dimensions

