

Product data sheet

Characteristics

8903SVG3V03

Contactor, Type S, multipole lighting,
electrically held, 200A, 4 pole, 220/240 VAC
50/60 Hz coil, NEMA 1



Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	240 V AC 60 Hz 220 V AC 50 Hz
Current Rating	200 A
Number of Poles	4P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	39.13 in (994 mm)
Depth	10.24 in (260 mm)
Width	22.17 in (563 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product Certifications	UL Listed CSA


Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	785901521747
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39.13 in (99.4 cm)
Package 1 Width	22.17 in (56.3 cm)
Package 1 Length	10.24 in (26.0 cm)
Package 1 Weight	9.75 lb(US) (4.424 kg)

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------