



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Number of cables	1
------------------	---

Physical

Color	Silver
Height	4.02 in (10.2 cm)
Width	5.98 in (15.2 cm)
Depth	5.98 in (15.2 cm)
Net Weight	5.03 lb(US) (2.28 kg)
Mounting Mode	Rack-mounted

Conformance

Product Certifications	CSA
Standards	UL 1778

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...15000 ft
Relative Humidity	5...95 %
Ambient Air Temperature for Storage	32...104 °F (0...40 °C)
Storage altitude	0...15000 ft (0.00...4572.00 m)
Storage Relative Humidity	5...95 %

Ordering and shipping details




GTIN	731304234838
------	--------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company at the time of publication. It is not intended to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.00 in (25.4 cm)
Package 1 Width	6.50 in (16.5 cm)
Package 1 Length	9.02 in (22.9 cm)
Package 1 Weight	6.04 lb(US) (2.74 kg)

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------