QOB31001042

Mini circuit breaker, QO, 100A, 3 pole, 120/240VAC, 10kA, bolt on mount, AC/DC shunt





Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	100 A
Voltage Rating	120/240 V AC 240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs
Options	Shunt trip 12/24 V AC/DC

Complementary

Interrupt Rating	10 KA 120/240 V AC 50/60 Hz	
, ,	10 KA 240 V AC 50/60 Hz	
	10 kA 120 V AC 50/60 Hz	
Number of Panel Spaces	4	
Wire Size	AWG 4AWG 2/0 copper or aluminium	
Tightening Torque	40.71 lbf.in (4.6 N.m)	
Height	3.50 in (89 mm)	
Width	2.99 in (76 mm)	
Depth	2.91 in (74 mm)	
Net Weight	1.36 lb(US) (0.617 kg)	

Environment

Certifications	UL Listed CSA	
Ambient Rating	104 °F (40 °C)	

Ordering and shipping details

Category	00015-QOB CIRCUIT BREAKERS
Discount Schedule	DE2
GTIN	785901168768
Returnability	No
Country of origin	MX

Packing Units

PCE	
1	
3.40 in (8.636 cm)	
3.20 in (8.128 cm)	
4.00 in (10.16 cm)	
21.76 oz (616.886 g)	
	1 3.40 in (8.636 cm) 3.20 in (8.128 cm) 4.00 in (10.16 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	☑ China RoHS Declaration
Halogen content performance	Halogen free product

Contractual warranty

Warranty 18 months		
	Warranty	18 months