



Main

Product or Component Type	Starter
Range of Product	Type S

Complementary

Control circuit	Separate control circuit
Control type	Without
NEMA degree of protection	NEMA 1 painted sheet steel
Auxiliary contact composition	Without
Maximum Horse Power Rating	200 V AC, 3 phase 230 V AC, 3 phase 460/575 V AC, 3 phase
Poles description	3P
Maximum operating voltage	600 V AC
NEMA size	0
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Local signalling	With pilot light
Motor starter type	2 speed
Electrical Connection	Lugs
Thermal overload type	Melting alloy
Number of thermal units required	6
Asynchronous motor control profile	Constant horsepower
Maximum operating current	18 A

Environment

Product Certifications	UL listed file E78351 CCN NLDX CSA LR60905 class 3211 04
------------------------	---


Ordering and shipping details

Category	21302 - 8810,11,12 S
Discount Schedule	CP1
GTIN	785901177258
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	26.60 lb(US) (12.066 kg)

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------