8536SAO12V02ES

NEMA Motor Starter, Type S, nonreversing, Size 00, 9A, 2 HP at 460 VAC, up to 65 kA SCCR, 3 phase, 3 pole, bimetal, 120 VAC coil, open



Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

Complementary		
NEMA Size	00	
Rated Current	9 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	IEC adapted Bi-metal	
Horsepower Rating	1.5 HP 200 V AC 1.5 HP 230 V AC 2 HP 460 V AC 2 HP 575 V AC	
SCCR	Circuit-breaker 15 A maximum, SCCR: 65 kA at 480 V AC Circuit-breaker 15 A maximum, SCCR: 50 kA at 600 V AC Fuse J 30 A maximum, SCCR: 65 kA at 600 V AC Fuse CC 30 A maximum, SCCR: 65 kA at 600 V AC	
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Control Circuit Type	Separate control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	6.81 in (172.96 mm)	
Width	3.50 in (88.90 mm)	
Depth	4.22 in (107.19 mm)	

Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901296997
Returnability	Yes
Country of origin	MX

Packing Units

3		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.60 in (11.684 cm)	
Package 1 Width	6.00 in (15.24 cm)	
Package 1 Length	8.10 in (20.574 cm)	
Package 1 Weight	3.47 lb(US) (1.574 kg)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months	