8736SAO16V02H308S

NEMA Starter, Type S, reversing, horizontal, Size 00, 9A, 2 HP at 575 VAC, up to 100 kA SCCR, 3 phase, 3 pole, Motor Logic SSOLR, 120 VAC coil, open



Main

Product Type	Starter	
Product Range	S	
Starter Type	Reversing	

Complementary

NEMA Size	00	
Rated Current	9 A	
Number of Poles	3P	
Mounting Orientation	Horizontal	
Wiring Mode	3 wires	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Solid state Motor Logic class 10/20	
Horsepower Rating	1.5 HP 200 V AC 1.5 HP 230 V AC 2 HP 460 V AC 2 HP 575 V AC	
SCCR	Circuit-breaker 70 A maximum: 100 kA at 480 V AC Fuse J 60 A maximum: 100 kA at 600 V AC Fuse T 60 A maximum: 100 kA at 600 V AC Fuse RK1 60 A maximum: 100 kA at 600 V AC Fuse RK5 60 A maximum: 100 kA at 600 V AC	
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Control Circuit Type	Separate control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	6.91 in (175.51 mm)	
Width	7.13 in (181.10 mm)	
Depth	5.31 in (134.87 mm)	

Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed CSA

Ordering and shipping details

Category	21271 - 8702,36 SA,SB(NOT S*R,T,W)	
Discount Schedule	CP1	
GTIN	785901777762	
Returnability	No	
Country of origin	MX	

Packing Units

PCE
1
6.93 in (17.6 cm)
7.13 in (18.1 cm)
5.31 in (13.5 cm)
8.00 lb(US) (3.629 kg)

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------