8538SBG11V81CF4T

NEMA Combination Starter, Type S, nonfusible disconnect, Size 0, 18A, 5 HP at 600 VAC polyphase, 120 VAC coil, NEMA 1



Main

Product	Combination Starter
Туре	S
Control Circuit Type	Control circuit transformer

Complementary

Complementary		
Control Circuit Voltage	120 V AC 60 Hz secondary circuit 480 V AC 60 Hz primary circuit	
Starter Type	Non reversing	
Number of Poles	3P	
Horsepower Rating	3 Hp 200 V AC, 3 phase 3 Hp 230 V AC, 3 phase 5 Hp 460 V AC, 3 phase 5 hp 575 V AC, 3 phase	
Maximum Voltage Rating	600 V AC	
Control Units	Selector switch HAND-OFF-AUTO)	
Pilot Light	No indicator	
Auxiliary Contacts	Without	
Control Circuit Fusing	2 fuses primary circuit	
Thermal overload type	Melting alloy 3	
Disconnect Type	Non-fusible disconnect switch	
NEMA size	0	

Environment

Enclosure Type	NEMA 1 painted sheet steel with external reset
LIIGIOSUIC I VDC	NEWA I painted sheet steel with external reset

Ordering and shipping details

Category	21212 - 8538,39SB(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	785901019640
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	45.00 lb(US) (20.412 kg)

Offer Sustainability

oHS Directive	Not compliant
a RoHS Regulation	☑ China RoHS Declaration
a RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months