



Main

| | |
|----------------------|-----------------------------|
| Product | Combination Starter |
| Type | S |
| Control Circuit Type | Control circuit transformer |

Complementary

| | |
|-------------------------|--|
| Control Circuit Voltage | 120 V AC 60 Hz secondary circuit 480 V AC 60 Hz primary circuit |
| Starter Type | Non reversing |
| Number of Poles | 3P |
| Horsepower Rating | 10 Hp 200 V AC, 3 phase 15 Hp 230 V AC, 3 phase 25 Hp 460 V AC, 3 phase 25 hp 575 V AC, 3 phase |
| Maximum Voltage Rating | 600 V AC |
| Control Units | Selector switch HAND-OFF-AUTO) |
| Pilot Light | Red indicator on incandescent |
| Auxiliary Contacts | 1 NO + 1 NC |
| Control Circuit Fusing | 2 fuses primary circuit 1 fuse secondary circuit |
| Thermal overload type | Melting alloy 3 |
| Disconnect Type | Non-fusible disconnect switch |
| NEMA size | 2 |


Environment

| | |
|----------------|--|
| Enclosure Type | NEMA 1 painted sheet steel with external reset |
|----------------|--|

Ordering and shipping details

| | |
|-------------------|------------------------------------|
| Category | 21213 - 8538,39 SC,SD(NOT S*R,T,W) |
| Discount Schedule | CP1 |
| GTIN | 00785901778394 |
| Returnability | No |
| Country of origin | MX |

Offer Sustainability

| | |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov |
| EU RoHS Directive | Not compliant |
| China RoHS Regulation |  China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|