Product data sheet Characteristics

861HSSR208-DD

Relay, SE Relays, solid state, SPST NO, 8A, 24...280 VAC, 3.5...32 VDC, MOSFET, hazardous locations approved



Main

Range	Legacy
Product Type	Solid state relay
Maximum output current	8 A DC
Mounting Support	Panel DIN rail
Network Number of Phases	1 phase
Output Voltage	3150 V DC
Control Circuit Voltage	3.532 V DC

Complementary

Complementary	
Holding Current	20 mA
Input Current Limits	12 mA at 5 V DC typical
Switch Function	SPST
Contacts Type and Composition	NO
Protection Technology	Current limiter
Protection Type	Reverse polarity protection
Tightening Torque	0.8 N.m for input/output
Connections Terminals	Input/output screw clamp terminal 0.00 in² (2.5 mm²) AWG 14)
Local Signalling	For input status 1 LED (green)
Switching Device	Mosfet output DC switching
Load Current	8 A at nominal load
Overload Current	17 A for 1 second
Surge Current	35 A 1 cycle
Must Release Voltage	1 V
Voltage Drop	<0.5 V on-state DC
Resistance	0.04 Ohm on-state
Thermal Resistance	0.5 °C/W
Leakage Current	0.1 mA at off-state 150 V DC
Response Time	5 ms (turn-off) 5 ms (turn-on)
Dielectric Strength	2500 V between input and output 2500 V between terminals and chassis
Height	2.56 in (65 mm)
Width	0.62 in (15.75 mm)
Depth	3.54 in (89.93 mm)
Product Weight	4.48 oz (127.1 g)
Device Presentation	Complete device

Environment

Product Certifications	CE CSA UL
IP Degree of Protection	IP20
Ambient Air Temperature for Operation	-22176 °F (-3080 °C)
Ambient Air Temperature for Storage	-40212 °F (-40100 °C)

Ordering and shipping details

Category	21127-ZELIO ICE CUBE RELAYS
Discount Schedule	CP2
GTIN	3606480282126
Returnability	Yes
Country of origin	IN


Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.64 in (9.24 cm)
Package 1 Width	0.69 in (1.76 cm)
Package 1 Length	2.56 in (6.5 cm)
Package 1 Weight	4.48 oz (127.1 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	1
Package 2 Height	2.56 in (6.5 cm)
Package 2 Width	0.63 in (1.6 cm)
Package 2 Length	3.94 in (10 cm)
Package 2 Weight	4.48 oz (127.1 g)
Unit Type of Package 3	CAR
Number of Units in Package 3	10
Package 3 Height	2.87 in (7.3 cm)
Package 3 Width	4.21 in (10.7 cm)
Package 3 Length	7.72 in (19.6 cm)
Package 3 Weight	2.80 lb(US) (1.271 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Approximate Dimensions



Connections and Wiring Diagrams

