HMIG5UL8A

base unit, Harmony GTU, Open BOX for Universal Panel, EcoStruxure Machine SCADA Expert, pre-installed





Main

Range of Product	Harmony GTU
Product or Component Type	Base unit
Device short name	Open Box
Range Compatibility	Harmony GTU
[Us] rated supply voltage	1224 V DC power supply

Complementary

Integrated connection type	Ethernet TCP/IP 2 RJ45
integrated connection type	COM1 serial link RJ45 RS485 110115200 bit/s
	COM2 serial link SUB-D 9 RS232C/RS422/RS485 110115200 bit/s
	Auxiliary port terminal block
	Expansion unit fieldbus card
	USB 2.0 port mini B USB
	DVI-D video port DVI-D
	Microphone mini-jack
	USB 2.0 port 3 USB type A
Communication port protocol	Modbus
	Modbus TCP/IP
	Uni-Telway
Operating system	Windows Embedded 7
Software package	Internet Explorer
	EcoStruxure machine SCADA expert trial version
	.NET framework 4.0
	Adobe PDF reader
	Multimedia player
	Office reader
	VNC client/server
Processor name	Intel X86 1.33 GHz
Data storage equipment	32 GB CFast card
Port Ethernet	10BASE-T/100BASE-TX/1000BASE-T
Memory description	512 kB NVRAM backup memory
	2 GB RAM internal
Type of cooling	Natural convection
Width	7.40 in (188 mm)
Height	5.16 in (131 mm)
Depth	1.77 in (45 mm)
Net Weight	1.98 lb(US) (0.9 kg)

Environment

Standards	CSA C22.2 No 142 ANSI/ISA 12-12-01 UL 508 Class I division 2 CSA C22.2 No 213 IEC 61132-2
Product certifications	CE CULus ATEX IEC-Ex RCM GL KC CUL EAC ABS BV CCS DNV LR RINA
Ambient air temperature for operation	32140 °F (060 °C)
Ambient air temperature for storage	-4140 °F (-2060 °C)
Pollution degree	2 EN 61131-2 Ed.3
Relative Humidity	1090 % non-condensing
Operating altitude	6561.68 ft (2000 m)
Vibration resistance	3.5 mm constant amplitude 59 Hz) EN/IEC 61131-2 9.8 m/s² 9150 Hz) EN/IEC 61131-2
Electromagnetic compatibility	Electrostatic discharge immunity testlevel 3 EN/IEC 61000-4-2

Ordering and shipping details

Category	22567-MAGELIS HMI GTU
Discount Schedule	MC2
GTIN	3606489504106
Returnability	No

Packing Units

T doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.31 in (13.5 cm)
Package 1 Width	8.27 in (21 cm)
Package 1 Length	10.24 in (26 cm)
Package 1 Weight	2.65 lb(US) (1.202 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	11.81 in (30 cm)
Package 2 Width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)
Package 2 Weight	17.04 lb(US) (7.728 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	36
Package 3 Height	28.58 in (72.6 cm)
Package 3 Width	23.62 in (60 cm)
Package 3 Length	31.50 in (80 cm)
Package 3 Weight	77.21 lb(US) (35.02 kg)

Offer Sustainability


Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.


Product data sheet Dimensions Drawings

HMIG5UL8A

Dimensions

External Dimensions





- 1 Front
- 2 Left
- 3 Bottom