

# Product data sheet

## Characteristics

# 8903SMW60V02

Contactor, Type S, combination lighting,  
electrically held, 30A, 3 pole, no fuse, 110/120  
VAC 50/60 Hz coil, NEMA 4/4X



## Main

Product	Combination electrically held lighting contactor
Type	S

## Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	30 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Disconnecter device type	Non-fusible disconnect switch
Electrical Connection	Lugs
Height	24.76 in (629 mm)
Depth	8.35 in (212 mm)
Width	9.49 in (241 mm)

## Environment

Enclosure Type	NEMA 4/4X brushed stainless steel surface none
Product Certifications	UL listed file E16151 CCN NRNT


## Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	785901462897
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.76 in (62.9 cm)
Package 1 Width	9.49 in (24.1 cm)
Package 1 Length	8.35 in (21.2 cm)
Package 1 Weight	33.36 lb(US) (15.132 kg)

Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------