# ZB6EH0B

Complete body for pilot lights, Harmony XB6, light block with body/fixing collar incandescent bulb <=24 V





#### Main

Range of Product	Harmony XB6
Product or Component Type	Complete body for pilot lights
Device short name	ZB6
Sale per indivisible quantity	5
Connections - terminals	Faston connectors 2.8 x 0.5 mm
Light source	Incandescent (bulb not included)
Bulb base	BA 9s
Light block supply	Direct
[Us] Rated Supply Voltage	<= 24 V AC/DC

#### Complementary

Terminals description ISO n°1	(X1-X2)PL
Net Weight	0.01 lb(US) (0.003 kg)
Operating position	Any position
[Ui] rated insulation voltage	250 V 2)EN/IEC 60947-1
[Uimp] rated impulse withstand voltage	4 kV EN 60947-1
Signalling type	Steady

#### Environment

LITTIONICITE		
Protective treatment	TC	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)	
Electrical shock protection class	Class II IEC 61140	
Standards	UL 508 EN/IEC 60947-5-5 EN/IEC 60947-1 JIS C 4520 CSA C22.2 No 14 JIS C 852 EN/IEC 60947-5-1	
Product Certifications	GOST UL CCC CSA	
Vibration resistance	+/- 3 mm 2500 Hz)IEC 60068-2-6 5 gn 2500 Hz)IEC 60068-2-6	
ock resistance 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27		

### Ordering and shipping details

Category	22459-PUSHBUTTONS, 16MM	
Discount Schedule	CS2	
GTIN	3389110784381	
Returnability	No	

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.87 in (2.2 cm)
Package 1 Width	1.30 in (3.3 cm)
Package 1 Length	2.56 in (6.5 cm)
Package 1 Weight	0.11 oz (3 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	0.87 in (2.2 cm)
Package 2 Width	1.30 in (3.3 cm)
Package 2 Length	2.56 in (6.5 cm)
Package 2 Weight	0.56 oz (16 g)
Unit Type of Package 3	S01
Number of Units in Package 3	200
Package 3 Height	5.91 in (15 cm)
Package 3 Width	5.91 in (15 cm)
Package 3 Length	15.75 in (40 cm)
Package 3 Weight	25.19 oz (714 g)

## Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead an lead compounds, which is known to the State of California to cause cance and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☐ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS  Declaration	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

#### Contractual warranty

- Contractadi Warranty		
Warranty	18 months	

# Product data sheet Dimensions Drawings

# ZB6EH0B

# Body for Pilot Light

#### Dimensions

