



TRANSFORMER SPECIFICATION

15kVA 3 PHASE 60 HERTZ
 PRIMARY VOLTAGE: 480V DELTA
 SECONDARY VOLTAGE: 480Y/277 WITH 6-TAPS
 150°C RISE ABOVE 40°C AMBIENT
 220°C INSULATION SYSTEM ALUMINUM WINDING
 APPROXIMATE WEIGHT: 191 LBS
 GUARANTEED SOUND LEVEL: 39 dB
 TYPE 2 ENCLOSURE PAINTED ANSI 49 GREY
 MINIMUM EFFICIENCY 97.89% @ 35% LOADING 75°C
 COMPLYING DOE 2016-10 CFR 431
 (78 FR 23335-APRIL 18, 2013)

SEISMIC QUALIFICATION

TO BE COMPLIANT WITH THE SEISMIC REQUIREMENTS OF ASCE/SEI 7.
 THIS UNIT IS SELF CERTIFIED TO ICS ES AC156 BY SHAKE TABLE
 QUALIFICATIONS TESTING. THE ENCLOSURE ABOVE IS 17M.

NOTES:

cULus LISTED TO UL1561 AND C22. 2No47, FILE NUMBER E6868.
 ALL UNITS 100% TESTED PRIOR TO SHIPPING TO NEMA ST-20 (2014).
 MANUFACTURED IN ISO 9001 FACILITIES.
 GREEN PREMIUM (RoHS/REACH COMPLAINT, PRODUCT ENVIRONMENTAL PROFILE).
 REGISTERED TO DOE VIA 10 CFR 429 & NRCAN
 MINIMUM CLEARANCE 1/2 INCH PER ALCOVE TESTING UL 1561. SIDES AND REAR
 FRONT ACCESS MUST COMPLY WITH NEC WORK SPACE REQUIREMENTS. MINIMUM
 CLEARANCE OF 6.00/[152].
 CONDUIT ENTRY AREA ARE SHOWN SHADED ABOVE, LOCATIONS ARE FRONT SIDES AND
 FRONT BOTTOM.

DUAL DIMENSIONS: INCHES
 MILLIMETERS

LOW VOLTAGE DISTRIBUTION TRANSFORMER,
 DOE 2016
 DRY TYPE TRANSFORMERS, CATALOG NUMBER EXN15T1814H
 3PH, 480 DELTA,
 SECONDARY 480Y/277 ALUMINUM

SQUARE D™
 by **Schneider Electric**

DWG# EXN15T1814H PG 1
 NO.