# 9001BF107

control station type B - 1 operator - universal (w/o legend ) - stainless plate





Main	
Range of Product	Harmony 9001B
Product or Component Type	Complete control station
Device short name	9001BF
Control station application	Two functions

Grey

#### Complementary

Complementary	
Material	Cast zinc
Marking	CE
Type of operator	momentary
Control station composition	1 push-button without marking
Contacts type and composition	1 NO + 1 NC
Mechanical durability	5000000 cycles
[le] rated operational current	5 A 600 V, AC
Device mounting	Flush
Type of Installation	Indoor

Colour of base of

enclosure

#### Environment

Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
NEMA degree of protection	NEMA 1
Product Certifications	UL listed file E42259 CCN NKCR CSA LR25490 class 3211 03

### Ordering and shipping details

0 11 0	
Category	21421-9001 B (NOT BW70 - BW80)
Discount Schedule	CS1
GTIN	785901390411
Returnability	No
Country of origin	MX

#### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	12.70 in (32.258 cm)	
Package 1 Width	5.00 in (12.7 cm)	
Package 1 Length	32.26 in (81.935 cm)	
Package 1 Weight	16.00 oz (453.592 g)	

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☐ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information

### Contractual warranty