Product data sheet Characteristics

8536SDG1V08A

NEMA Motor Starter, Type S, nonreversing, Size 2, 45A, 25 HP at 460 VAC, 5 kA SCCR, 3 phase, 3 pole, melting alloy, 208 VAC coil, NEMA 1

Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

Complementary		
NEMA Size	2	
Rated Current	45 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Melting alloy 3	
Horsepower Rating	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC	
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC	
Coil Voltage	208 V AC 60 Hz	
Control Circuit Type	Common control circuit	
Control Units	2 momentary push-buttons (START-STOP)	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	12.69 in (322.33 mm)	
Width	7.81 in (198.37 mm)	
Depth	6.31 in (160.27 mm)	

Environment

Enclosure Type	NEMA 1 painted sheet steel
Certifications	UL Listed CSA NEMA

Ordering and shipping details

21192 - 8502,36 SC,SD(NOT S*R,T,W)
CP1
785901899785
No
MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.68 in (32.2 cm)
Package 1 Width	7.80 in (19.8 cm)
Package 1 Length	6.30 in (16.0 cm)
Package 1 Weight	9.25 lb(US) (4.196 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
PVC free	Yes

Contractual warranty

Warranty	18 months