# 9001SKR8P1

Illuminated push-button head, Harmony 9001SK, plastic, without mushroom, 30mm, 3 positions, return to center, 110-120V







Main	
Range of Product	Harmony 9001SK
Product or Component Type	Head for illuminated push-button
Device short name	9001SK

Complementary

Bezel material	Plastic
Mounting diameter	1.18 in (30 mm)
Contacts type and composition	Without contact block
Mechanical durability	5000000 cycles
Device presentation	Basic element
Cap/operator or lens colour	Without mushroom
[Us] rated supply voltage	110120 V
Light block supply	Via integral transformer
Type of operator	Pull : spring return, center : stay put, push : spring return
Operator position information	3 positions
Supply frequency	5060 Hz
Size	30 mm
Bulb base	BA 9s
Light source	Incandescent bulb

#### Environment

LITTIONICH		
Standards	EN/IEC 60947-1	
	CSA C22.2 No 14	
	JIS C 852	
	JIS C 4520	
	UL 508	
	EN/IEC 60947-5-4	
	EN/IEC 60947-5-1	
IP degree of protection	IP66	
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13	

### Ordering and shipping details

Category	21429-9001 SK,SKY
Discount Schedule	CS1
GTIN	785901042952
Returnability	No

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.08 in (12.903 cm)
Package 1 Width	2.00 in (5.08 cm)
Package 1 Length	12.90 in (32.774 cm)
Package 1 Weight	8.00 oz (226.796 g)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

#### Contractual warranty

Contraction warranty		
Warranty	18 months	