9001KR9P1W

Illuminated push-button head, Harmony 9001K, metal, mushroom 41mm, white, 30mm, 2 positions, push-pull, 110-120V





Main

| Range of Product | Harmony 9001K |
|------------------------------|----------------------------------|
| Product or Component Type | Head for illuminated push-button |
| Device short name | 9001K |
| Type of operator | push-pull |
| Operator profile | White mushroom Ø 41 mm, unmarked |
| | |

Complementary

| complementary | | |
|---------------------------------|--|--|
| Bezel material | Metal | |
| Mounting diameter | 1.18 in (30 mm) | |
| Net Weight | 0.43 lb(US) (0.195 kg) | |
| Operating position | Any position | |
| Shape of signaling unit head | Round | |
| Head material | Plastic | |
| Operator additional information | Screw-on plastic | |
| Operator position information | 2 positions | |
| Contacts type and composition | Without contact block | |
| Mechanical durability | 5000000 cycles | |
| Light source | incandescent | |
| Bulb base | BA 9s | |
| Light block supply | Via integral transformer 110120 V AC 50/60 Hz 6 V) | |
| Device presentation | Basic element | |
| Cap/operator or lens colour | White | |
| [Us] rated supply voltage | 110120 V | |
| Light block supply | Via integral transformer | |
| Operator profile | Mushroom Ø 41 mm | |
| Type of operator | Push-pull | |
| Supply frequency | 5060 Hz | |
| Size | 30 mm | |
| Light source | Incandescent bulb | |
| | | |

Environment

| Protective treatment | TC |
|---------------------------------------|----------------------|
| Ambient Air Temperature for Storage | -40158 °F (-4070 °C) |
| Ambient Air Temperature for Operation | -13158 °F (-2570 °C) |
| Overvoltage category | Class II IEC 61140 |
| IP degree of protection | IP66 IEC 60529 |

| NEMA degree of protection | NEMA 1 |
|-------------------------------|---|
| | NEMA 12 |
| | NEMA 13 |
| | NEMA 2 NEMA 3 |
| | NEMA 3R |
| | NEMA 4 |
| | NEMA 6 |
| Standards | EN/IEC 60947-5-1 |
| | EN/IEC 60947-1 EN/IEC 60947-5-4 |
| | JIS C 4520 |
| | JIS C 852 |
| | UL 508 |
| | CSA C22.2 No 14 |
| Product Certifications | NEMA UL 508 |
| N/II - 0: | |
| /ibration resistance | 7 gn 2500 Hz)IEC 60068-2-6 |
| Shock resistance | 50 gn IEC 60068-2-27 |
| Ordering and shipping details | |
| Category | 21426-9001 K (NOT KA,KM,KX) |
| Discount Schedule | CS1 |
| GTIN | 785901034223 |
| Returnability | No |
| • | |
| Packing Units | |
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.08 in (12.903 cm) |
| Package 1 Width | 2.00 in (5.08 cm) |
| Package 1 Length | 12.90 in (32.774 cm) |
| Package 1 Weight | 8.00 oz (226.796 g) |
| | |
| Offer Sustainability | |
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and |
| | lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to |
| | www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | |
| - | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free | Yes |
| China RoHS Regulation | [™] China RoHS Declaration |
| RoHS exemption information | © Yes |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific |
| | waste collection and never end up in rubbish bins. |
| | |
| Contractual warranty | |
| Marranti | 10 months |

18 months

Warranty