# Product data sheet Characteristics

## EZML313225D

Branch unit, EZ Meter-Pak, 225A, 3 sockets, 208Y/120VAC, lever bypass, ringless, 1200A busbar, drip hood

#### Main

Product	Meter Center Branch Unit
Current Rating	225 A
Туре	Meter-Pak
Bus Rating	1200 A
Number of Jaws	5 with jaw release
Number of Meter Sockets	3
Bypass Type	Lever bypass
Socket Type	Ringless

#### Complementary

Certifications	UL Listed	
Busbar Material	Aluminium/copper busbar	
Enclosure Material	Steel	
Enclosure Rating	NEMA 3R	
Maximum Voltage Rating	208Y/120 V AC	
Mounting	Surface	
Phase	3 phase in 1 phase out	
Wire Configuration	4-wire	
Contact status	Closed	
Device Composition	Drip hood	
Height	53.06 in (1347.72 mm)	
Width	19.44 in (493.78 mm)	
Depth	9.44 in (239.78 mm)	

#### Ordering and shipping details

Category	00020-EZ METER-PAK
Discount Schedule	DE4
GTIN	785901343677
Returnability	No
Country of origin	MX

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	53.07 in (134.8 cm)	
Package 1 Width	19.45 in (49.4 cm)	
Package 1 Length	9.45 in (24.0 cm)	
Package 1 Weight	164.00 lb(US) (74.389 kg)	

#### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	€Yes

#### Contractual warranty

oonaastaan marranty	
Warranty	18 months