# HU364DS

Safety switch, heavy duty, non fusible, 200A, 3 wire, 3 poles, 150hp, 600VAC/DC, Type 4, 4X, 5, 304 stainless steel





### Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	3
Current Rating	200 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 4/4X/5 stainless steel 304
Motor power hp	15 Hp at 240 V AC 50-60 Hz for 1 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors 50 Hp at 480 V AC 50-60 Hz for 1 phase motors 125 Hp at 480 V AC 50-60 Hz for 3 phase motors 50 Hp at 600 V AC 50-60 Hz for 1 phase motors 150 Hp at 600 V AC 50-60 Hz for 3 phase motors 40 Hp at 250 V DC 50 hp at 600 V DC

### Complementary

Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire
Wire Size	AWG 6250 kcmil copper or aluminium
Tightening torque	275 lbf.in (31.07 N.m) 0.020.20 in² (13.3127 mm²) (AWG 6250 kcmil)
Depth	8.88 in (225.55 mm)
Width	19.25 in (488.95 mm)
Height	29 in (736.60 mm)
Net Weight	55.01 lb(US) (24.95 kg)

#### **Environment**

Certifications	UL listed file E2875

# Ordering and shipping details

Category	00010-H&HU SW,2&3P,N4,SS,30-200A
Discount Schedule	DE1
GTIN	785901023746
Returnability	Yes
Country of origin	US

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	10.60 in (26.924 cm)	
Package 1 Width	20.20 in (51.308 cm)	
Package 1 Length	32.60 in (82.804 cm)	
Package i Length	32.00 IN (82.804 CM)	

Package 1 Weight	55.15 lb(US) (25.016 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	6
Package 2 Height	35.50 in (90.17 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	342.00 lb(US) (155.128 kg)

# Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

### Contractual warranty

Warranty	18 months