



Note:

- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

HDL36125



by Schneider Electric

Schneider Electric United States  
North American Division  
Boston One Campus  
800 Federal Street  
Andover, MA 01810, USA  
Phone: +1 8773425173  
Email: CCC@us.schneider-electric.com

Technical Information:

General Application: Provides overload and short circuit protection  
For Use With: Industrial Enclosures and Switchboards  
Approvals: UL Listed - CSA Certified - IEC Rated  
Mounting Type: Unit Mount  
Terminal Type: Line: Lug - Load: Lug  
Wire Size: #14-3/0 AWG (Al/Cu)  
Weight: 5 Pounds  
Depth: 4.36 Inches  
Height: 6.40 Inches  
Width: 4.12 Inches

Description: PowerPact H-frame Thermal Magnetic Circuit Breaker  
Number of Poles: 3-Pole  
Ampere Rating: 125A  
Voltage Rating: 600VAC/250VDC  
Interrupting Rating: 25kA at 240VAC - 18kA at 480VAC - 14kA at 600VAC - 20kA at 250VDC  
Circuit Breaker Rating: 80% Rated  
Fixed AC Magnetic Trip: Hold: 900A - Trip: 1700A

Specification: