Product data sheet Characteristics

8536SGA1V03

NEMA Motor Starter, Type S, nonreversing, Size 5, 270A, 200 HP at 460 VAC, 3 phase, 3 pole, melting alloy, 240 VAC coil, NEMA 1, 10 kA SSCR2

Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

o o mpromornary		
NEMA Size	5	
Rated Current	270 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Melting alloy 3	
Horsepower Rating	75 HP 200 V AC 100 HP 230 V AC 200 HP 460 V AC 200 HP 575 V AC	
SCCR	Circuit-breaker: 10 kA at 600 V AC Fuse: 10 kA at 600 V AC	
Coil Voltage	220 V AC 50 Hz 240 V AC 60 Hz	
Control Circuit Type	Common control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	47.00 in (1193.80 mm)	
Width	17.22 in (437.39 mm)	
Depth	13.44 in (341.38 mm)	

Environment

Enclosure Type	NEMA 12 painted sheet steel
Certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21194 - 8502,36SG(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	785901408260
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	47.01 in (119.4 cm)	
Package 1 Width	17.20 in (43.7 cm)	
Package 1 Length	13.43 in (34.1 cm)	
Package 1 Weight	32.00 lb(US) (14.515 kg)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	[™] China RoHS Declaration

Contractual warranty

	The state of the s
Warranty	18 months
vvarianty	16 months