Q0116M100PC

Load center, QO, 1 phase, 16 spaces, 24 circuits, 100A convertible main breaker, PoN, NEMA1, combo cover, UL





Main

IVICIII	
Marketing Trade Name	QO
Product Type	Load Center
Cover Type	Combination flush/surface cover
Provided Equipment	Cover

Complementary

Tightening Torque	Cover 20 lb.in	
PoN Convertible Mains (lugs)	PoN Convertible Mains (breaker)	
Rated Current	100 A	
Number of Spaces	16	
Max Short Circuit Current Rating	22 kA	
Maximum Number of Single Pole Circuits	24	
Maximum Number of Tandem Breakers	8	
Number of Phases	1 phase	
Ground Bar	Grounding bar (ordered separately)	
Box Number	6	
Height	17.92 in (455.17 mm)	
Width	14.25 in (361.95 mm)	
Depth	3.75 in (95.25 mm)	

Environment

Enclosure Rating	NEMA 1 indoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering and shipping details

10001-QO PON 1PH LC,12-60 CKT, MB N1
DE3A
785901085881
Yes
US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.74 in (9.5 cm)
Package 1 Width	14.25 in (36.2 cm)
Package 1 Length	17.91 in (45.5 cm)
Package 1 Weight	18.96 lb(US) (8.6 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile