# 8536SDG2V03

NEMA Motor Starter, Type S, nonreversing, Size 2, 45A, 25 HP at 460 VAC, 5 kA SCCR, 2 phase, 4 pole, melting alloy, 240 VAC coil, NEMA 1



#### Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

o in promornary		
NEMA Size	2	
Rated Current	45 A	
Number of Poles	4P	
Maximum Voltage Rating	600 V AC	
Phase	2 phases	
Type of Overload	Melting alloy 2	
Horsepower Rating	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC	
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC	
Coil Voltage	220 V AC 50 Hz 240 V AC 60 Hz	
Control Circuit Type	Common control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	12.69 in (322.33 mm)	
Width	7.81 in (198.37 mm)	
Depth	6.31 in (160.27 mm)	

#### Environment

Enclosure Type	NEMA 1 painted sheet steel
Certifications	UL Listed CSA NEMA

## Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)	21192 - 8502,36 SC,SD(NOT S*R,T,W)	
Discount Schedule	CP1		
GTIN	785901757733		
Returnability	No		
Country of origin	MX		

### Packing Units

PCE
1
9.40 in (23.876 cm)
13.40 in (34.036 cm)
14.60 in (37.084 cm)
9.25 lb(US) (4.196 kg)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	€Yes	
PVC free	Yes	

#### Contractual warranty

Contraction training		
Warranty	18 months	