

Product data sheet

Characteristics

8903SVG61V02

Contactor, Type S, combination lighting,
electrically held, 3 pole, 200A, 600 V fuse,
110/120 VAC 50/60 Hz coil, NEMA 1



Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	200 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	50.00 in (1270 mm)
Depth	10.67 in (271 mm)
Width	15.98 in (406 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product Certifications	UL listed file E16151 CCN NRNT


Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	785901153702
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	50.00 in (127.0 cm)
Package 1 Width	15.98 in (40.6 cm)
Package 1 Length	10.67 in (27.1 cm)
Package 1 Weight	113.00 lb(US) (51.256 kg)

Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------