



Main

| | |
|----------------------|--------------------------|
| Product | Combination Starter |
| Type | S |
| Control Circuit Type | Separate control circuit |

Complementary

| | |
|-------------------------|--|
| Control Circuit Voltage | 110 V AC 50 Hz 120 V AC 60 Hz |
| Starter Type | Non reversing |
| Line Rated Current | 18 A |
| Number of Poles | 3P |
| Horsepower Rating | 5 Hp 460 V AC, 3 phase 5 hp 575 V AC, 3 phase |
| Maximum Voltage Rating | 600 V AC |
| Control Units | No control units |
| Auxiliary Contacts | Without |
| Thermal overload type | Solid state Motor Logic class 10/20 3...9 A |
| Disconnect Type | Fusible disconnect switch H and K, 30 A |
| NEMA size | 0 |
| Height | 22.5 in (571.50 mm) |
| Depth | 8.34 in (211.84 mm) |
| Width | 9.5 in (241.30 mm) |
| Handle Swing | 3.25 in (82.55 mm) |

Environment

| | |
|------------------------|--|
| Enclosure Type | NEMA 1 painted sheet steel with external reset |
| Product Certifications | CSA UL Listed |


Ordering and shipping details

| | |
|-------------------|------------------------------------|
| Category | 21212 - 8538,39SB(NOT S*R,S*T,S*W) |
| Discount Schedule | CP1 |
| GTIN | 785901840190 |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 45.00 lb(US) (20.412 kg) |

Offer Sustainability

| | |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov |
| EU RoHS Directive | Under investigation |
| China RoHS Regulation |  China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|