ACF25EC

End Closure, I-Line Busway, max 5000A rated, end caps





Main

Product	End Closure
Range	I-Line

Complementary

Rated Operational Voltage	600 V AC/DC 50/60 Hz	
Length	25.6 in (650.24 mm)	
Height	7.06 in (179.32 mm)	
Width	1 in (25.40 mm)	
For Use with	Busbar trunking 5000 A copper end caps	

Environment

Standards	UL 857 CSA C22.2 No 27:1994	
	IEC 61439-6	

Ordering and shipping details

Category	20199-WALL FLANGES/END CLOSURES
Discount Schedule	PE8
GTIN	785901816263
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.59 in (65.0 cm)
Package 1 Width	0.98 in (2.5 cm)
Package 1 Length	7.05 in (17.9 cm)
Package 1 Weight	15.92 lb(US) (7.221 kg)

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☐ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

18 months