# SC8L125F

Meter mains, Homeline, CSED, ringed socket, 125A, semi flush mount, maximum 8 spaces, no bypass





Main	
Product or Component Type	Meter Mains
Range of Product	Homeline

Complementary

o o mpromornary		
Line Rated Current	125 A	
Short-circuit current	10 kA	
Network number of phases	1	
Meter socket type	Ringed	
Mounting	Semi flush	
Number of spaces	8	
Number of circuits	0	
Number of Tandem Breakers	0	
Hub type	A B300	
Electrical connection	Lugs line side Lugs service ground	
Wire Size	AWG 6AWG 2/0 aluminium/copper)line side AWG 6AWG 2/0 aluminium/copper)service ground	
Disconnect	Service disconnect (ordered separately)	
Main Breaker Rating	110 A	
Service feed location	OH UG	
Bypass type	No bypass	
Height	26.42 in (671.07 mm)	
Width	14.50 in (368.30 mm)	
Depth	3.40 in (86.36 mm)	

#### Environment

Product certifications UL E-6294			
	FIGURE	UL E-6294	

### Ordering and shipping details

Category	00048-HOM METER MAINS
Discount Schedule	DE3A
GTIN	785901111481
Returnability	Yes

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	26.42 in (67.1 cm)
Package 1 Width	14.49 in (36.8 cm)
Package 1 Length	3.39 in (8.6 cm)
Package 1 Weight	37.00 lb(US) (16.783 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	<sup>™</sup> REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€ Yes
Environmental Disclosure	Product Environmental Profile
	Product Environmental Profile

### Contractual warranty

Warranty	18 months