# 8536SGO1V08

NEMA Motor Starter, Type S, nonreversing, Size 5, 270A, 200 HP at 460 VAC, 3 phase, 3 pole, melting alloy, 208 VAC coil, open, 10 kA SSCR



#### Main

Product Type	Motor starter	
Product Range	S	
Starter Type	Non reversing	

Complementary

NEMA Size	5	
Rated Current	270 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Melting alloy 3	
Horsepower Rating	75 HP 200 V AC 100 HP 230 V AC 200 HP 460 V AC 200 HP 575 V AC	
SCCR	Circuit-breaker: 10 kA at 600 V AC Fuse: 10 kA at 600 V AC	
Coil Voltage	208 V AC 60 Hz	
Control Circuit Type	Common control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	17.56 in (446.02 mm)	
Width	8.56 in (217.42 mm)	
Depth	8.75 in (222.25 mm)	

#### Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed CSA NEMA

### Ordering and shipping details

Category	21194 - 8502,36SG(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	785901879343
Returnability	No
Country of origin	MX

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.56 in (44.6 cm)
Package 1 Width	8.54 in (21.7 cm)
Package 1 Length	8.74 in (22.2 cm)
Package 1 Weight	32.00 lb(US) (14.515 kg)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Not compliant	
China RoHS Regulation	<sup>™</sup> China RoHS Declaration	

## Contractual warranty

144	10 11	
Warrantv	18 months	
vvarianty	10 11011113	
•		