

8539SCA54S8V06

NEMA Combination Starter, Type S, HHL
electronic motor circuit protector, Size 1, 27A, 3
phase, 480 VAC coil, NEMA 12



Main

Product	Combination Starter
Type	S
Control Circuit Type	Common control circuit

Complementary

Control Circuit Voltage	440 V AC 50 Hz 480 V AC 60 Hz
Starter Type	Non reversing
Number of Poles	3P
Horsepower Rating	0.25...5 Hp 200 V AC, 3 phase 0.25...7.5 Hp 230 V AC, 3 phase 0.25...10 Hp 460 V AC, 3 phase 0.25...10 hp 575 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	No control units
Pilot Light	No indicator
Auxiliary Contacts	Without
Thermal overload type	Melting alloy 3
Disconnect Type	Circuit breaker, 30 A
Circuit breaker type	EMCP
Breaking capacity	100 KA 480 V AC 35 kA 600 V AC
Height	31 in (787.40 mm)
Depth	10.97 in (278.64 mm)
Width	15 in (381.00 mm)
Handle Swing	3.25 in (82.55 mm)

Environment

Enclosure Type	NEMA 12 painted sheet steel with external reset
NEMA size	1
Product Certifications	CSA file 584 class 3211 04 UL listed file E152395 CCN NKJH7 UL listed file E152395 CCN NKJH

Ordering and shipping details

Category	21213 - 8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901532590
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.98 in (78.7 cm)
Package 1 Width	15.00 in (38.1 cm)
Package 1 Length	10.98 in (27.9 cm)
Package 1 Weight	45.00 lb(US) (20.412 kg)

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------