QO120M200P

Load center, QO, 1 phase, 20 spaces, 30 circuits, 200A convertible main breaker, PoN, NEMA1, UL





Main

Wall		
Marketing Trade Name	QO	
Product Type	Load Center	

Complementary

Tightening Torque	Cover 20 lb.in	
PoN Convertible Mains (lugs)	PoN Convertible Mains (breaker)	
Rated Current	200 A	
Number of Spaces	20	
Max Short Circuit Current Rating	22 kA	
Maximum Number of Single Pole Circuits	30	
Maximum Number of Tandem Breakers	10	
Number of Phases	1 phase	
Ground Bar	Grounding bar (ordered separately)	
Box Number	9	
Height	29.84 in (758 mm)	
Width	14.25 in (362 mm)	
Depth	3.74 in (95 mm)	
Net Weight	25.99 lb(US) (11.790 kg)	

Environment

Enclosure Rating	NEMA 1 indoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering and shipping details

Category	10001-QO PON 1PH LC,12-60 CKT, MB N1
Discount Schedule	DE3A
GTIN	785901607410
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.74 in (9.5 cm)
Package 1 Width	14.25 in (36.2 cm)
Package 1 Length	29.84 in (75.8 cm)
Package 1 Weight	15.00 lb(US) (6.804 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile