

## Product data sheet

### Characteristics

## 8903SQH1V02

Contactor, Type S, multipole lighting,  
electrically held, 100A, 2 pole, 110/120 VAC  
50/60 Hz coil, NEMA 3R



### Main

Product	Electrically Held Lighting Contactor
Type	S

### Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	100 A
Number of Poles	2P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	25.31 in (643 mm)
Depth	8.62 in (219 mm)
Width	12.83 in (326 mm)

### Environment

Enclosure Type	NEMA 3R Stainless Steel surface none
Product Certifications	UL listed file E16151 CCN NRNT

### Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	785901024033
Returnability	No
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.31 in (64.3 cm)
Package 1 Width	12.83 in (32.6 cm)
Package 1 Length	8.62 in (21.9 cm)
Package 1 Weight	9.75 lb(US) (4.424 kg)

Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------