QOB25035

Mini circuit breaker, QO, 50A, 2 pole, 120/240VAC, 10kA, bolt on mount, 50 degrees C





Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	50 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs

Complementary

10 KA 120/240 V AC 50/60 Hz	
10 kA 120 V AC 50/60 Hz	
2	
AWG 8AWG 2 copper or aluminium	
40.71 lbf.in (4.6 N.m)	
3.11 in (79 mm)	
1.50 in (38 mm)	
2.91 in (74 mm)	
0.61 lb(US) (0.277 kg)	
	10 kA 120 V AC 50/60 Hz 2 AWG 8AWG 2 copper or aluminium 40.71 lbf.in (4.6 N.m) 3.11 in (79 mm) 1.50 in (38 mm) 2.91 in (74 mm)

Environment

Environment		
Certifications	UL Listed CSA	:
Ambient Rating	122 °F (50 °C)	:

Ordering and shipping details

Category	00015-QOB CIRCUIT BREAKERS
Discount Schedule	DE2
GTIN	785901754053
Returnability	No
Country of origin	MX

Packing Units

50 in (3.81 cm)
30 in (8.382 cm)
50 in (8.89 cm)
76 oz (276.691 g)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	proposition 65 WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer. For information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Halogen content performance	Halogen free product	

Contractual warranty

Warranty	18 months