

8903SVO12V02

Contactor, Type S, multipole lighting,
mechanically held, 200A, 4 pole, 110/120 VAC
50/60 Hz coil, open style



Main

Product	Mechanically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	200 A
Number of Poles	4P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	9.13 in (232 mm)
Depth	6.73 in (171 mm)
Width	9.76 in (248 mm)

Environment

Enclosure Type	Not rated (open device) surface none
Product Certifications	UL Listed CSA

Ordering and shipping details

Category	30156-8903 S:ELEC HELD LTG CONTR
Discount Schedule	SQ2L
GTIN	785901835318
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.13 in (23.2 cm)
Package 1 Width	9.76 in (24.8 cm)
Package 1 Length	6.73 in (17.1 cm)
Package 1 Weight	18.24 lb(US) (8.274 kg)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------