8536SBG2V06E

NEMA Motor Starter, Type S, nonreversing, Size 0, 18A, 5 HP at 460 VAC, up to 65 kA SCCR, 3 phase, 3 pole, bimetal, 480 VAC coil, NEMA 1



Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

NEMA	^	
NEMA Size	0	
Rated Current	18 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	IEC adapted Bi-metal	
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC	
SCCR	Circuit-breaker 35 A maximum, SCCR: 65 kA at 480 V AC Circuit-breaker 35 A maximum, SCCR: 50 kA at 600 V AC Fuse J 60 A maximum, SCCR: 65 kA at 600 V AC Fuse CC 60 A maximum, SCCR: 65 kA at 600 V AC	
Coil Voltage	440 V AC 50 Hz 480 V AC 60 Hz	
Control Circuit Type	Common control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	10.00 in (254.00 mm)	·
Width	6.00 in (152.40 mm)	
Depth	5.56 in (141.22 mm)	

Environment

Enclosure Type	NEMA 1 painted sheet steel
Certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901732402
Returnability	Yes
Country of origin	MX

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.80 in (14.732 cm)
Package 1 Width	6.50 in (16.51 cm)
Package 1 Length	11.50 in (29.21 cm)
Package 1 Weight	7.14 lb(US) (3.239 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☑ China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months	