



KNOCKOUTS							
SYMBOL	A	B	C	D	E	F	G
IN	.50	.75	1.00	1.25	1.50	2.00	2.50
MM	13	19	25	32	38	51	64



QO112L125PWG



QO120L125PWG

- NOTES:
1. INTERIOR SHIFTED LEFT
 2. RIGHT SIDE WIRE GUTTER
4.00/[102] WIDE AND
3.75/[95] DEEP

DUAL DIMENSIONS: INCHES
MILLIMETERS

CATALOG NUMBER	MAXIMUM SYSTEM VOLTAGE	MAINS AMPERE RATING	SPACES	MAXIMUM NUMBER OF SINGLE POLE CIRCUITS	MAIN WIRE SIZE AWG AL/CU
QO112L125PWG	120/240VAC 1Ø 3W	125	12	24	#6-2/0
QO120L125PWG			20		

NOTES:

FINISH — GRAY BAKED ENAMEL ELECTRODEPOSITED OVER CLEANED PHOSPATIZED STEEL.

UL LISTED — FILE E-6294

NEUTRALS — INSULATED GROUNDABLE.

QO LOAD CENTERS
GENERAL PURPOSE NEMA TYPE 1 ENCLOSURE
INDOOR



by Schneider Electric

DWG# PWFDS-SYRS-0229
NO.