

CH364RB

Safety switch, heavy duty, fusible, 200A, 600 VAC/VDC, 3 poles, 150hp, NEMA 3R, bolt on provision



Main

Product	Single Throw Safety Switch
Disconnect Type	Fusible disconnect
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty

Complementary

Line Rated Current	200 A
Factory Installed Neutral	None
Mounting Type	Surface
Voltage Rating	600 V AC/DC
Motor power hp	50 Hp at 480 V AC 50-60 Hz for 3 phase motors 125 Hp at 480 V AC 50-60 Hz for 3 phase motors 60 Hp at 600 V AC 50-60 Hz for 3 phase motors 150 Hp at 600 V AC 50-60 Hz for 3 phase motors 40 Hp at 250 V DC 50 hp at 600 V DC
Wire Size	AWG 6...250 kcmil copper or aluminium
Tightening torque	275 lbf.in (31.07 N.m) 0.02...0.20 in ² (13.30...127 mm ²) (AWG 6...250 kcmil)
Height	29.25 in (742.95 mm)
Width	18.63 in (473.20 mm)
Depth	8.5 in (215.90 mm)

Environment

Certifications	cUL
Enclosure Rating	NEMA 3R galvanized steel

Ordering and shipping details

Category	00153-C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	785901995463
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.60 in (21.844 cm)
Package 1 Width	19.30 in (49.022 cm)
Package 1 Length	30.40 in (77.216 cm)
Package 1 Weight	55.50 lb(US) (25.174 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes