



TERMINAL LUGS			
AMPERES	MAX WIRE	MIN WIRE	TYPE
100	1/0 AWG	#14	AL

KNOCKOUTS			
SYMBOL	CONDUIT SIZE		DIAMETER
	IN	MM	IN MM
A	.50	13	.88 22
B	.75	19	1.13 29
C	1.00	25	1.38 35
D	1.25	32	1.75 44
E	1.50	38	2.00 51
F	2.00	51	2.50 64

DUAL DIMENSIONS: INCHES  
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATING	AMPERE RATING	WIRING DIAG	240 VAC				CORNER ③ GROUNDED DELTA SYSTEM		480 VAC				CORNER ③ GROUNDED DELTA SYSTEM		600 VAC				125 VDC ②		250 VDC ②		600 VDC ②	
				1PH ①		3PH		STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	1PH ①							
				STD	MAX	STD	MAX											STD	MAX	STD	MAX	STD	MAX	STD	MAX
DT223RB	240	100	A	7.5	15	NA	NA	15	30	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	20	NA	NA	NA
DT323RB	240	100	B	7.5	15	15	30	15	30	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	20	NA	NA	NA
DT363RB	600	100	B	7.5	15	15	30	15	30	10	30	25	60	25	60	15	40	30	75	NA	NA	NA	20	40	50

NOTES:  
 ① UL LISTED - FILE E-2875  
 FINISH - GRAY BAKED ENAMEL  
 ALL NEUTRALS - INSULATED  
 SHORT CIRCUIT CURRENT RATING:  
 10,000 AMPERES WHEN USED IN CONJUNCTION WITH CLASS H OR K FUSES.  
 200,000 AMPERES WHEN USED IN CONJUNCTION WITH CLASS J OR R FUSES.  
 ② FOR SINGLE PHASE HP RATINGS USE 2 SWITCHING POLES.  
 ③ FOR DC RATINGS USE 2 SWITCHING POLES.  
 ④ FOR CORNER GROUNDED DELTA SYSTEM, USE 2 SWITCHING POLES AND INSTALL NEUTRAL FOR GROUNDED CONDUCTOR.

HEAVY DUTY SAFETY SWITCHES  
 VISIBLE BLADES  
 100 AMPERE  
 ENCLOSURE - TYPE 3R  
 FUSIBLE



DWG# 3201  
NO.