



TERMINAL LUGS			
AMPERES	MAX WIRE	MIN WIRE	TYPE
100	1/0 AWG	#14	AL

KNOCKOUTS			
SYMBOL	CONDUIT SIZE		DIAMETER
	IN	MM	IN
A	.50	13	.88
B	.75	19	1.13
C	1.00	25	1.38
D	1.25	32	1.75
E	1.50	38	2.00
F	2.00	51	2.50

CATALOG NUMBER	VOLTAGE RATING	AMPERE RATING	WIRING DIAG	240 VAC				CORNER ③ GROUNDED DELTA SYSTEM		480 VAC				CORNER ③ GROUNDED DELTA SYSTEM		600 VAC				125 VDC ②		250 VDC ②		600 VDC ②		
				1PH ①		3PH		STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	
				STD	MAX	STD	MAX																			STD
DT223RB	240	100	A	7.5	15	NA	NA	15	30	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	20	NA	NA	NA	NA
DT323RB	240	100	B	7.5	15	15	30	15	30	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	20	NA	NA	NA	NA
DT363RB	600	100	B	7.5	15	15	30	15	30	10	30	25	60	25	60	15	40	30	75	NA	NA	NA	20	40	50	

NOTES:
 UL LISTED - FILE E-2875
 FINISH - GRAY BAKED ENAMEL
 ALL NEUTRALS - INSULATED
 SHORT CIRCUIT CURRENT RATING:
 10,000 AMPERES WHEN USED IN CONJUNCTION WITH CLASS H OR K FUSES.
 200,000 AMPERES WHEN USED IN CONJUNCTION WITH CLASS J OR R FUSES.
 ① FOR SINGLE PHASE HP RATINGS USE 2 SWITCHING POLES.
 ② FOR DC RATINGS USE 2 SWITCHING POLES.
 ③ FOR CORNER GROUNDED DELTA SYSTEM, USE 2 SWITCHING POLES AND INSTALL NEUTRAL FOR GROUNDED CONDUCTOR.

HEAVY DUTY SAFETY SWITCHES
 VISIBLE BLADES
 100 AMPERE
 ENCLOSURE - TYPE 3R
 FUSIBLE



DWG# 3201
 NO.