



TERMINAL LUGS			
AMPERES	MAX. WIRE	MIN. WIRE	TYPE
1200	(4) 750 KCMIL	(4) #3/0 AWG	75°C AL OR CU

FUSE PROVISIONS			
AMPERES	TYPE	AMPERES	TYPE
1200	CLASS "L"	800	CLASS "L"

* SIDE ENTRY/EXIT MUST MEET ALL APPLICATION STANDARDS AND CODES.

NOTES: FINISH - GRAY BAKED ENAMEL-ANSI #49
 ALL NEUTRALS - INSULATED GROUNDABLE (SHIPPED CARTONED FOR FIELD INSTALLATION)
 UL LISTED - FILE E-154828
 CSA CERTIFIED - FILE LL-97406-3
 SUITABLE FOR USE AS SERVICE EQUIPMENT UNLESS A 600/347V OR 480/277V, 1000A OR GREATER, SOLIDLY GROUND WYE SYSTEM REQUIRING GROUND FAULT PROTECTION IS USED.
 SHORT CIRCUIT RATING:
 200,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS L FUSES.
 75 LBS. MAX. FORCE REQUIRED TO OPERATE HANDLE.
 FOR NEMA TYPE 3R APPLICATIONS 1/4-20 DRAIN SCREW MUST BE REMOVED FROM BOTTOM ENDWALL.

DUAL DIMENSIONS: INCHES
 MILLIMETERS

CATALOG NUMBER	VOLTAGE RATINGS	WIRING DIAG.	3 PHASE HORSEPOWER RATINGS						DC HORSEPOWER RATINGS	
			240VAC		480VAC		600VAC		250VDC	
			STD.	MAX.	STD.	MAX.	STD.	MAX.	50	100
H328AWK	240VAC; 250VDC	A	100	250	-	-	-	-	50	-
H328NAWK	240VAC; 250VDC	B	100	250	-	-	-	-	50	-
H368AWK	600VAC; 600VDC	A	-	-	200	500	250	500	50	50
H368NAWK	600VAC; 600VDC	B	-	-	200	500	250	500	50	50
HU368AWK	600VAC; 600VDC	C	100	250	200	500	250	500	50	50

HEAVY DUTY SAFETY SWITCHES
 VISIBLE BLADE TYPE
 1200 AMPERE
 ENCLOSURE - NEMA TYPE 12
 NEMA TYPE 3R RAINPROOF
 NEMA TYPE 5 DUST TIGHT (INDOOR)

SQUARE D COMPANY

DWG. NO. 2176