CH221NAWK

Safety switch, heavy duty, fusible, 30A, 240 VAC/250VDC, 2 poles, 7.5hp, NEMA 12, neutral





Main

Product	Single Throw Safety Switch	
Disconnect Type	Fusible disconnect	
Number of Poles	2	
Electrical Connection	Lugs	
Duty Rating	Heavy duty	

Complementary

Complementary		
Line Rated Current	30 A	
Factory Installed Neutral	Neutral (factory installed)	
Mounting Type	Surface	
Voltage Rating	240 V DC 250 V AC	
Motor power hp	1.5 Hp at 240 V AC 50-60 Hz for 1 phase motors 3 Hp at 240 V AC 5060 kHz for 3 phase motors 3 Hp at 240 V AC 5060 kHz for 1 phase motors 7.5 Hp at 240 V AC 5060 kHz for 3 phase motors 5 hp at 250 V DC	
Wire Size	AWG 12AWG 6 aluminium AWG 14AWG 6 copper	
Tightening torque	45 Lbf.In (5.08 N.m) 0.02 in² (13.3 mm²) (AWG 6) 40 Lbf.In (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 35 lbf.in (3.95 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)	
Height	16.5 in (419.10 mm)	
Width	10.5 in (266.70 mm)	
Depth	7 in (177.80 mm)	

Environment

Certifications	CSA
Enclosure Rating	NEMA 3R/12 galvannealed steel

Ordering and shipping details

Category	00153-C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	785901994831
Returnability	Yes
Country of origin	US


Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.50 in (13.97 cm)
Package 1 Width	8.00 in (20.32 cm)
Package 1 Length	17.50 in (44.45 cm)
Package 1 Weight	10.30 lb(US) (4.672 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	80
Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	36.00 in (91.44 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	825.54 lb(US) (374.459 kg)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

Approximate Dimensions



CH221NAWK

Connections and Wiring Diagrams

WIRING DIAGRAMS			
FUSIBLE		NOT FUSIBLE	
	1	7-7-7	
H221AWK	H321AWK H361AWK	HU361AWK HU361AWKEI	