



TERMINAL LUG DATA ±			
AMPERES	MAX WIRE	MIN WIRE	TYPE
200	250 KCMIL	#6 AWG	CU/AL

DUAL DIMENSIONS: INCHES
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS													
			240VAC				480VAC				600VAC				250 VDC	600 VDC
			STD		MAX		STD		MAX		STD		MAX		STD	STD
			2 Ø	3 Ø	2 Ø	3 Ø	2 Ø	3 Ø	2 Ø	3 Ø	2 Ø	3 Ø	2 Ø	3 Ø		
H464DS	600VAC;600VDC	A	30	25	50	60	50	50	—	125	50	60	—	150	40	50
H664DS	600VAC;600VDC	C	15▲	25	—	60	25▲	50	50▲	125	30▲	60	50▲	150	40	50
HU464DS	600VAC;600VDC	B	—	—	50	60	—	—	50	125	—	—	50	150	40<	50<
HU664DS	600VAC;600VDC	D	—	—	15▲	60	—	—	50▲	125	—	—	50▲	150	40<	50<

NOTES:
 FINISH — TYPE 304 STAINLESS STEEL
 UL LISTED — E2875
 SHORT CIRCUIT CURRENT RATINGS:
 10,000 AMPERES WITH CLASS H OR K FUSES.
 200,000 AMPERES WITH CLASS R OR J FUSES.
 ON 600V SWITCHES, 100,000 AMPERES MAX ON CORNER GROUNDED DELTA WHEN PROTECTED BY
 CLASS J OR R FUSES, 200 AMPERE MAX.
 NOT SUITABLE FOR USE AS SERVICE EQUIPMENT
 ± LUGS SUITABLE FOR 75°C CONDUCTORS.
 ▲ 1Ø RATING
 < MAX RATING

HEAVY DUTY SAFETY SWITCHES
 VISIBLE BLADE TYPE
 200 AMPERE — SERIES F6
 ENCLOSURE — NEMA 4, 4X AND 5 STAINLESS STEEL

SQUARE D COMPANY

DWG# 3231
NO.