# **CH361**

**Duty Rating** 

Safety switch, heavy duty, fusible, 30A, 600 VAC/VDC, 3 poles, 20hp, NEMA 1





Main	
Product	Single Throw Safety Switch
Disconnect Type	Fusible disconnect
Number of Poles	3
Electrical Connection	Lugs

Heavy duty

Complementary

Complementary	
Line Rated Current	30 A
Factory Installed Neutral	None
Mounting Type	Surface
Voltage Rating	600 V AC/DC
Motor power hp	5 Hp at 480 V AC 50-60 Hz for 3 phase motors 15 Hp at 480 V AC 50-60 Hz for 3 phase motors 7.5 Hp at 600 V AC 50-60 Hz for 3 phase motors 20 Hp at 600 V AC 50-60 Hz for 3 phase motors 5 Hp at 250 V DC 15 hp at 600 V DC
Wire Size	AWG 12AWG 6 aluminium AWG 14AWG 6 copper
Tightening torque	45 Lbf.In (5.08 N.m) 0.02 in² (13.3 mm²) (AWG 6) 40 Lbf.In (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 35 lbf.in (3.95 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)
Height	14.6 in (370.84 mm)
Width	7.55 in (191.77 mm)
Depth	4.87 in (123.70 mm)

#### Environment

Certifications	CSA
Enclosure Rating	NEMA 1 galvannealed steel

### Ordering and shipping details

Category	00153-C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	785901995142
Returnability	Yes
Country of origin	US

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.30 in (13.462 cm)
Package 1 Width	7.80 in (19.812 cm)
Package 1 Length	16.10 in (40.894 cm)
Package 1 Weight	8.04 lb(US) (3.647 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	<sup>™</sup> China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes