# XU2N18KP9AAL5T

Photoelectric sensors XU, XU2, transmitteur, cylindrical M18, 15 m





#### Main

Range of Product	Telemecanique Photoelectric sensors XU
Series name	Application food and beverage
Electronic sensor type	Photo-electric sensor
Sensor name	XU2
Sensor design	Cylindrical M18
Detection system	Thru beam
Material	Stainless steel
Type of output signal	Discrete
Supply circuit type	DC
Wiring Technique	3-wire
Discrete output function	1 NO or 1 NC programmable
Electrical connection	Cable
Cable length	82.02 ft (25 m)
Emission	Infrared thru beam
[Sn] nominal sensing distance	49.21 ft (15 m) thru beam

### Complementary

Enclosure Material	Stainless steel : 304 CU	
Lens material	PMMA	
Maximum sensing distance	65.62 ft (20 m)	
Output Type	Solid state	
[Us] rated supply voltage	24240 V AC/DC	
Supply voltage limits	1030 V DC	
Switching capacity in mA	<= 100 mA overload and short-circuit protection)	
Switching frequency	<= 500 Hz	
Maximum voltage drop	<1.5 V closed state)	
Current consumption	<= 50 mA no-load	
Maximum delay first up	15 ms	
Maximum delay response	1 ms	
Maximum delay recovery	1 ms	
Setting-up	Sensitivity adjustment	
Diameter	0.71 in (18 mm)	
Length	3.46 in (88 mm)	

#### Environment

Product Certifications	CSA	
	UL	
	CE	
Ambient air temperature for operation	-13131 °F (-2555 °C)	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Vibration resistance	7 gn +/- 1.5 mm 1055 Hz) IEC 60068-2-6	
Shock resistance	30 gn 11 ms) IEC 60068-2-27	
IP degree of protection	IP67 IEC 60529	

## Ordering and shipping details

Category	22481-SENSORS, PHOTOELECTRIC
Discount Schedule	DS2
GTIN	3389118380929
Returnability	Yes
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.83 in (14.8 cm)	
Package 1 Width	3.19 in (8.1 cm)	
Package 1 Length	3.19 in (8.1 cm)	
Package 1 Weight	8.47 oz (240.0 g)	

## Offer Sustainability

Offer Sustamability		
Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	