# Product data sheet Characteristics

# 9007MS12S0054

# Limit switch, 9007, 240 VAC 10amp ms +options



#### Main Range of Product 9007 Series name Miniature potted **Product or Component** Limit switch Type Device short name 9007MS/ML Sensor design Miniature Body type Fixed Plunger head Head type Material Metal

Cast zinc

1

Complementary

Complementary	
Fixing Mode	By the body
Movement of operating head	Linear
Type of operator	Spring return parallel roller plunger steel booted
Type of approach	Lateral approach, 2 directions
Switch actuation	By 30° cam
Contacts type and composition	NC-NO
Switch Function	SPDT
Contact form	Form C
Contacts material	Silver contacts
Contact operation	Snap action
Positive opening	Without
Electrical connection	Male connector M12 micro DC type 4 pins bottom
Terminals description ISO n°1	(3-4)NC (1)Gnd (2-4)NO
Maximum force for tripping	80 ozf
[le] rated operational current	3 A 28 V DC 3 A 120 V AC 3 A 240 V AC
[Ithe] conventional enclosed thermal current	3 A
[Ui] rated insulation voltage	300 V 3)UL 508 300 V 3)CSA C22.2 No 14
Electrical durability	100000 cycles
Mechanical durability	10000000 cycles
Marking	UL CE CSA
Sale per indivisible quantity	1
Height	1.75 in (44.45 mm)
Width	1.56 in (39.62 mm)
Depth	0.62 in (15.75 mm)
Product Weight	1.2 lb(US) (0.54 kg)

**Body Material** 

Number of poles

#### Environment

Shock resistance	35 gn 9 ms IEC 60068-2-27
Vibration resistance	10 gn 751200 Hz)IEC 60068-2-6
NEMA degree of protection	NEMA 1 Nema type 250 NEMA 2 Nema type 250 NEMA 4 Nema type 250 NEMA 6 Nema type 250 NEMA 6P Nema type 250
IP degree of protection	IP67 conforming to IEC 60529
Ambient Air Temperature for Operation	-40220 °F (-40104 °C)
Ambient Air Temperature for Storage	-40220 °F (-40104 °C)
Protective treatment	Epoxy powder coat
Product Certifications	CE UL CSA
Standards	LR 25490 Class 32 11 03 E78403

## Ordering and shipping details

22431-LIMIT SWITCHES,TYPE 9007MS
DS1
785901187714
No
MX

# Packing Units

PCE
1
1.80 in (4.572 cm)
2.10 in (5.334 cm)
3.60 in (9.144 cm)
19.20 oz (544.311 g)

## Offer Sustainability

vn to the State of California n. For more information go to

### Contractual warranty

Warranty	18 months