


UL / cULus LISTED - FILE E-136861
SUITABLE FOR USE AS SERVICE EQUIPMENT. (CB125NAWK IN CANADA - cUL).
ENCLOSURE SUPPLIED WITH DUAL COVER INTERLOCK
NEUTRAL - INSULATED GROUNDABLE.
CB125NAWK IS EQUIPPED WITH SEALING PROVISIONS AND CONTAINS FACTORY INSTALLED AND BONDED SN225KA NEUTRAL AND
IS SUITABLE FOR USE AS SERVICE EQUIPMENT IN CANADA.
●KNOCKOUTS NEMA/EEMAC TYPE 12K ONLY
THE SHORT CIRCUIT CURRENT RATING OF THIS ENCLOSED CIRCUIT BREAKER IS EQUAL TO THE INTERRUPTING
RATING, AT THE SUPPLY VOLTAGE MARKED ON THE CIRCUIT BREAKER INSTALLED.
ENCLOSURE ACCEPTS 2 & 3 POLE BREAKERS ONLY.
ENCLOSURES ACCEPT STANDARD 80% RATED OR 100% RATED CIRCUIT BREAKERS. WHEN USING 100% RATED CIRCUIT
BREAKERS USE ONLY WITH 90°C (MIN) RATED WIRE SIZED PER AMPACITY OF 75°C RATED CONDUCTOR.



CIRCUIT BREAKER TERMINAL LUG DATA					
CIRCUIT BREAKER CATALOG NO. PREFIX	AMPERE RATING	CONDUCTORS PER PHASE	WIRE SIZE (AWG) (mm ²)		TYPE
			MAX.	MIN.	
BD	15 - 125 15 - 125	1	#3/0 95	#14 2.5	CU / AL
BG	15 - 125 15 - 125	1	#3/0 95	#14 2.5	CU / AL
BJ	15 - 125 15 - 125	1	#3/0 95	#14 2.5	CU / AL
BK	15 - 30 15 - 30	1	#3/0 95	#14 2.5	CU / AL

KNOCKOUTS				
SYMBOL	CONDUIT SIZE		DIAMETER	
	IN	MM	IN	MM
C	1.00	25	1.38	35
D	1.25	32	1.75	45
E	1.50	38	2.00	51
F	2.00	51	2.50	64

FIELD INSTALLABLE NEUTRAL ASSEMBLY AND GROUND KIT						
CATALOG NUMBER	MAXIMUM AMPERE RATING	NUMBER OF TERMINALS	WIRE SIZE (AWG)		TYPE	
			MAX.	MIN.		
SN100FA	15—100A	2	1 - IN 1 - OUT	#1/0 #1/0	#12 #14	AL CU
SN225KA	110—125A	2	1 - IN 1 - OUT	#1/0 #1/0	#12 #14	AL CU
PKOGTA2	—	2	1 - IN 1 - OUT	#1/0 #1/0	#6 #10	AL CU

● B125A
NEMA/EEMAC TYPE 12K

B125AWK
NEMA/EEMAC TYPE 12/3R

B125DS (304)
NEMA/EEMAC TYPE 4, 4X & 5

CB125NAWK
NEMA/EEMAC TYPE 12/3R

FIELD INSTALLED CIRCUIT BREAKER DATA #								
CIRCUIT BREAKER CATALOG NO. PREFIX	WIRING DIAGRAM	AMPERE RATING	UL LISTED INTERRUPTING RATING RMS SYMMETRICAL AMPERES (kA)					
			Vac					Vdc
			208Y/120	240	480Y/277	480	600Y/347	
BD	A	15 - 125	25	25	18	18	14	10
	B	15 - 125	25	25	18	18	14	10
BG	A	15 - 125	65	65	35	35	18	20
	B	15 - 125	65	65	35	35	18	20
BJ	A	15 - 125	100	100	65	65	25	50
	B	15 - 125	100	100	65	65	25	50
BK	A	15 - 30	100	100	65	65	65	—
	B	15 - 30	100	100	65	65	65	—

DUAL DIMENSIONS: MILLIMETERS [INCHES]

CIRCUIT BREAKER ENCLOSURES
15 - 125 AMPERE
NEMA/EEAC TYPE 12K, 12/3R INDUSTRIAL ENCLOSURE
NEMA/EEAC TYPE 4, 4X & 5 INDUSTRIAL ENCLOSURE

SQUARE D

by Schneider Electric

DWG.	PWCCB-ENCCB-0021
NO.	