### Product data sheet Characteristics

# ZC2JC2H29

Limit switch body, Limit switches XC Standard, ZC2J, fixed, without display, 2C/O, M20



#### Main Range of Product Telemecanique Limit switches XC Standard Series name Standard format **Product or Component** Limit switch body Type Device short name ZC2J Body type Fixed **Product Compatibility** XC2J ZC2JE63 Associated head ZC2JE09 ZC2JE05 ZC2JE01 ZC2JE61 ZC2JE02 ZC2JE70 ZC2JE03 ZC2JE65 ZC2JE66 ZC2JE62 ZC2JE64 **Body Material** Metal Cable entry 1 entry tapped for M20 x 1.5 cable gland Number of poles

2 C/O

Snap action

1 1 position

Silver plated contacts

#### Complementary

Local display	Without
Electrical connection	Screw-clamp terminals 1 x 0.752 x 1.5 mm²
Positive opening	Without
Minimum actuation speed	0.01 m/min
[le] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A 0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	500 VIEC 60947-1 contact block 300 VCSA C22.2 No 14 contact block
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3
Short-circuit protection	10 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13 120 V, 4 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 10 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Width	1.57 in (40 mm)
Height	3.19 in (81 mm)
Depth	1.61 in (41 mm)
Product Weight	0.78 lb(US) (0.355 kg)
Terminals description ISO n°1	(23-24)NO (13-14)NO (21-22)NC (11-12)NC

Contacts type and

Number of steps

Contacts material

composition

Contact operation

#### Environment

IP Degree of Protection	IP65
IK Degree of Protection	IK08
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment

### Ordering and shipping details

Category	22449-LIMIT SWITCHES,ACCESSORIES
Discount Schedule	Т
GTIN	3389110514797
Returnability	No
Country of origin	FR

### Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.77 in (4.5 cm)	
Package 1 Width	1.97 in (5.0 cm)	
Package 1 Length	3.74 in (9.5 cm)	
Package 1 Weight	12.28 oz (348.0 g)	

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile

### Contractual warranty

Warranty	18 months