Product data sheet Characteristics

ZCMD21L1

Limit switch body, Limit switches XC Standard, ZCMD, 1NC+1 NO, silver, snap action, connection, 1 m





Main

Series name Standard format Product or Component Type Device short name ZCMD Design Miniature Body type Fixed Associated head ZCE24 ZCE08 ZCE21 ZCE07 ZCEF0 ZCE02 ZCE13 ZCE62 ZCE62 ZCE65 ZCE64 ZCE01 ZCE99 ZCE09
Type Device short name ZCMD Design Miniature Body type Fixed Associated head ZCE24 ZCE08 ZCE21 ZCE07 ZCE70 ZCE70 ZCE60 ZCE02 ZCE13 ZCE62 ZCE65 ZCE64 ZCE01 ZCE29
Design Miniature Body type Fixed Associated head ZCE24 ZCE08 ZCE21 ZCE07 ZCEF0 ZCE62 ZCE13 ZCE62 ZCE65 ZCE64 ZCE01 ZCE01 ZCE29
Body type Fixed Associated head ZCE24 ZCE08 ZCE21 ZCE07 ZCE07 ZCEF0 ZCE02 ZCE02 ZCE13 ZCE62 ZCE65 ZCE64 ZCE01 ZCE01 ZCE01
Associated head ZCE24 ZCE08 ZCE21 ZCE07 ZCEF0 ZCE602 ZCE13 ZCE62 ZCE65 ZCE64 ZCE01 ZCE01 ZCE01
ZCE08 ZCE21 ZCE07 ZCEF0 ZCEF0 ZCE02 ZCE13 ZCE62 ZCE65 ZCE64 ZCE01 ZCE01 ZCE29
ZCE06 ZCEG1 ZCE66 ZCE14 ZCE10 ZCEF2 ZCE63 ZCE28 ZCE27 ZCE11 ZCE67
Body Material Zamak
Number of poles 2
Contacts type and 1 NC + 1 NO composition
Contact operation Snap action

Complementary

Product Compatibility	XCMD
Electrical connection	Removable cable
Cable length	3.28 ft (1 m)
Cable composition	5 x 0.75 mm²
Wire insulation material	PvR
Contacts insulation form	Zb
Contacts material	Silver plated contacts
Positive opening	With
Minimum actuation speed	0.01 m/min
[Ui] rated insulation voltage	300 V 3)UL 508 400 V 3)IEC 60947-5-1 300 V 3)CSA C22.2 No 14
Maximum resistance across terminals	25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	4 KV IEC 60664 4 kV IEC 60947-1

Short-circuit protection	6 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13 120 V, 3 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 4 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 3 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Width	1.18 in (30 mm)
Height	1.97 in (50 mm)
Depth	0.63 in (16 mm)
Product Weight	0.14 lb(US) (0.065 kg)

Environment

Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
-------------------------------------	----------------------

Ordering and shipping details

Category	22413-LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	Т
GTIN	3389110299267
Returnability	Yes
Country of origin	ID

Packing Units

r doming office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	5.12 in (13.0 cm)
Package 1 Length	5.51 in (14.0 cm)
Package 1 Weight	5.64 oz (160.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	60
Package 2 Height	11.81 in (30 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	22.65 lb(US) (10.275 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	480
Package 3 Height	30.31 in (77.0 cm)
Package 3 Width	23.62 in (60.0 cm)
Package 3 Length	31.50 in (80.0 cm)
Package 3 Weight	200.63 lb(US) (91.004 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEN RoHS
Mercury free	Yes
RoHS exemption information	€ Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Warranty 18 months