ZC2JE62

Limit switch head, Limit switches XC Standard, ZC2J, steel roller plunger





Main Range of Product OsiSense XC Series name Special format Limit switch head **Product or Component** Type ZC2J Device short name Head type Plunger head **Product Compatibility** XC2J Associated body ZC2JD1 ZC2JC1 ZC2JC28 ZC2JD2 ZC2JC2 ZC2JC18 Movement of operating Linear

Roller plunger spring return metal

Lateral approach, 2 directions

Complementary

Switch actuation	By 30° cam	
Positive opening	Without	
Product Weight	0.44 lb(US) (0.2 kg)	
Head material	Metal	

head

Type of operator

Type of approach

Environment

Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22449-LIMIT SWITCHES,ACCESSORIES
Discount Schedule	T
GTIN	3389110324044
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.97 in (5.0 cm)	
Package 1 Width	3.70 in (9.4 cm)	
Package 1 Length	1.89 in (4.8 cm)	
Package 1 Weight	7.55 oz (214.0 g)	
Unit Type of Package 2	S01	
Number of Units in Package 2	14	
Package 2 Height	5.91 in (15.0 cm)	
Package 2 Width	5.91 in (15.0 cm)	

Package 2 Length	15.75 in (40.0 cm)	
Package 2 Weight	7.04 lb(US) (3.193 kg)	
Offer Sustainability		
Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

	,
\	40
vvarranty	18 months