





## Main

|                           |                                          |
|---------------------------|------------------------------------------|
| Range of Product          | Telemecanique Limit switches XC Standard |
| Series name               | Standard format                          |
| Product or Component Type | Limit switch head                        |
| Device short name         | ZCE                                      |
| Head type                 | Plunger head                             |
| Product Compatibility     | XCKT<br>XCMD<br>XCKP<br>XCKD             |

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Associated body            | ZCP29<br>ZCD39<br>ZCP26<br>ZCMD69C12<br>ZCD21M12<br>ZCMD29L2<br>ZCMD39L5<br>ZCD27<br>ZCMD29C12<br>ZCT25G11<br>ZCT28N12<br>ZCMD21M12<br>ZCP21M12<br>ZCD28<br>ZCMD61C12<br>ZCT27N12<br>ZCMD21C12<br>ZCMD81L5<br>ZCT27G11<br>ZCT26P16<br>ZCMD21L2<br>ZCT25N12<br>ZCP25<br>ZCP29M12<br>ZCT27P16<br>ZCT21P16<br>ZCD35<br>ZCMD41L2<br>ZCD29M12<br>ZCMD25L5<br>ZCMD21L08U78<br>ZCT21G11<br>ZCT28G11<br>ZCP31<br>ZCMD37L5<br>ZCD29<br>ZCT26N12<br>ZCMD39L2<br>ZCP21<br>ZCT25P16<br>ZCP37<br>ZCMD61M12<br>ZCD37<br>ZCP39<br>ZCMD25L2<br>ZCMD37L2<br>ZCP35<br>ZCT26G11<br>ZCD26<br>ZCMD41L1<br>ZCD25<br>ZCMD29L1<br>ZCMD39L1<br>ZCP27<br>ZCMD41L5<br>ZCMD81L2<br>ZCD31<br>ZCMD37L1<br>ZCMD21L1<br>ZCMD29L5<br>ZCMD25L1<br>ZCMD21L5<br>ZCT28P16<br>ZCD21<br>ZCP28<br>ZCMD81L1<br>ZCT21N12<br>ZCMD21L08R12 |
| Movement of operating head | Linear                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Type of operator           | Roller lever plunger spring return metal retractable)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Type of approach           | Lateral approach, 1 direction                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

### Complementary

|                  |            |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | With       |

## Environment

|                                       |                            |
|---------------------------------------|----------------------------|
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C) |
| Environmental characteristic          | Standard environment       |

## Ordering and shipping details

|                   |                                    |
|-------------------|------------------------------------|
| Category          | 22413-LIMIT SWITCH, IEC, MINIATURE |
| Discount Schedule | T                                  |
| GTIN              | 3389110190830                      |
| Returnability     | Yes                                |
| Country of origin | ID                                 |

## Packing Units

|                              |                       |
|------------------------------|-----------------------|
| Unit Type of Package 1       | PCE                   |
| Number of Units in Package 1 | 1                     |
| Package 1 Height             | 0.60 in (1.52 cm)     |
| Package 1 Width              | 2.80 in (7.11 cm)     |
| Package 1 Length             | 4.30 in (10.92 cm)    |
| Package 1 Weight             | 0.79 lb(US) (0.36 kg) |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                                                                                                             |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                                                                                                                 |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                                                                                                    |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                                                                                                               |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                                                                                                               |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                                                                                                                     |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|